Version G_6.0 2024/01/09

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ECO-SOL MAX, ESL3-CY ECO-SOL MAX, ESL3-4CY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Inkjet Printing

1.3. Details of the supplier of the safety data sheet

Manufacturer's name: Roland DG Corporation

Address: 1-1-2 Shinmiyakoda, Hamana-ku, Hamamatsu-shi, Shizuoka-ken, 431-2103

Phone: +81-53-484-1224 FAX: +81-53-484-1226

E-mail:

Revised date: 9-Jan-2024

1.4. Emergency telephone:

2. Hazard identification

2.1. Classification of the substance or mixture

This product is classified as hazardous according to GHS.

Flammable liquids

Acute toxicity (oral)

Skin corrosion/irritation

Category 2

Serious eye damage/eye irritation

Category 1

Reproductive toxicity

Category 1B

2.2. GHS label elements, including precautionary statements

Pictgram(s)



Signal Word: Danger

Hazard Statement:

Combustible liquid.

Version G_6.0 2024/01/09

May be harmful if swallowed.

Causes skin irritation.

Causes serious eye damage.

May damage fertility or the unborn child.

Precautionary statements — **Prevention:**

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements — **Response:**

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Potential Health Effects:

Eyes: Causes severe eye injury which may persist for several days.

Skin: Contact with skin may cause irritation, swelling or redness, allergic sensitization.

Inhalation: Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired

fertility and irritate nose, throat/respiratory system.

Ingestion: May cause injury of mouth, throat, and stomach.

Chronic Health Hazards: Repeated skin contact may cause a persistent irritation or dermatitis.

Carcinogenicity: None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

Others: No information.

3. Composition/information on ingredients

Chemical nature: mixture

Composition	CAS No.	% By Weight	GHS Classification
Colorant	CBI	1-5	Not classified as hazardous
Diethylene glycol diethyl ether	112-36-7	55-65	Skin Irrit. 2: H315
γ-butyrolactone	96-48-0	<20	Acute Tox. 4: H302 Eye Damage 1: H318 STOT Single Exp. 3: H336
bis(2-(2-methoxyethoxy)ethyl) ether	143-24-8	10-20	Repr. 1B: H360
Tetraethylene glycol monobutyl ether	1559-34-8	1-5	Eye Irrit. 2: H319

[†] CBI: Confidential Business Information

[‡] For the full text of the H-Statements mentioned in this Section, see Section 16.



Version G 6.0 2024/01/09

4. First aid measures

4.1. Description of first aid measures

Eyes: In case of contact, immediately flush eyes with plenty of water for several minutes. Hold eyelids open

during flushing. Call a physician.

Skin: In case of contact, immediately flush with plenty of water while removing contaminated clothing and

shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give

oxygen. Call a physician.

If swallowed, DO NOT induce vomiting. Seek immediate medical advice. Ingestion:

4.2. Most important symptoms and effects, both acute and delayed

Eyes: Causes severe eye injury which may persist for several days.

Skin: Contact with skin may cause irritation, swelling or redness, allergic sensitization.

Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired fertility and Inhalation:

irritate nose, throat/respiratory system.

May cause injury of mouth, throat, and stomach. Ingestion:

4.3. Indication of any immediate medical attention and special treatment needed

no information

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Dry chemical, Foam, Carbon dioxide, Dry sand, Loaded stream in spray.

Unsuitable extinguishing media:

Water, High-pressure water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors. Flash Point: > 71deg.C

5.3. Advice for firefighters

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues. Applying direct water may be dangerous because fire may expand to surroundings.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate personal protective equipment.

Version G_6.0 2024/01/09

6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.

6.3. Methods and material for containment and cleaning up

Sweep up material and dispose as waste following local regulations.

6.4. Reference to other sections

Refer to "Section 8 Exposure controls/ personal protection" and "Section 13 Disposal consideration" as appropriate.

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Put protection wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with metals, amines, free radical initiators, oxidising agents.

7.3 Specific end use(s): Inkjet Printing

8. Exposure controls/ personal protection

8.1. Control parameters

Occupational Exposure Limits:

Derived No-Effect Level (DNEL)

— Diethylene glycol diethyl ether:

[Long term exposure] 50.05 mg/m³

[Short term exposure] no hazard identified

— γ-butyrolactone:

[Long term exposure] 130 mg/m³

[Short term exposure] 958 mg/m³

8.2. Exposure controls

Appropriate engineering controls

Provide general and/or local exhaust ventilation.

Respiratory protection:

Not requiredwhen sufficient ventilation is provided. In case of inadequate ventilation and exposure limits are exceeded or if irritation or other symptoms are experienced, use a NIOSH/MSHA or European Standard EN149 approved respirator (with activated carbon layer for organic vapour).

Hand protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, use protective gloves. Recommended impervious gloves is EN420/374 approved butyl rubber glove.



Version G_6.0 2024/01/09

Eye protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear EN166 approved safety glasses.

Skin protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear protective clothing.

Hygiene measures:

Wash hands after handling. In case contact with clothing, wash before reuse. Do not eat, drink or smoke in handling or storage area.

Environmental exposure control:

Avoid release to the environment.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Cyan Liquid
Odour: Slightly odour
Odour threshold: Not defined
pH: Not applicable
Melting point/freezing point: No data available
Initial boiling point and boiling range: No data available

Flash point: > 71deg.C

Evaporation rate: No data available Flammability (solid, gas) Not applicable Upper/lower flammability or explosive limits: No data available Vapor pressure: No data available

Vapor density: > 1
Relative density: 0.9-1.0
Solubility(ies): soluble

Partition coefficient: n-octanol/water:

Auto-ignition temperature:

No data available

Decomposition temperature:

No data available

Viscosity:

No data available

Explosive properties:

No data available

No data available

No data available

Volatile organic compounds (VOC) content: 950 g/L

9.2 Other information

No information.

Version G_6.0 2024/01/09

10. Stability and reactivity

10.1 Reactivity:

No reactivity under normal temperature.

10.2 Chemical stability:

Stable under normal temperature.

10.3 Possibility of hazardous reactions:

Not expected.

10.4 Conditions to avoid:

Elevated temperatures/heat, UV light, when not in use.

10.5 Incompatible materials:

Avoid contact with acids, amines, free radical initiators, oxidizing agents.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity:

γ-butyrolactone

LD50 (oral): 1582mg/kgbw, LD50 (dermal): no data available, LD50 (Inhal.): LC50>5.1mg/L

Serious eye damage/eye irritation:

Causes serious eye damage.

• γ-butyrolactone

Causes serious eye irritation.

• Tetraethylene glycol monobutyl ether

Skin corrosion/irritation:

Causes skin irritation.

• Diethylene glycol diethyl ether

Respiratory or skin sensitisation:

no data available.

Germ cell mutagenicity:

no data available.

Reproductive toxicity:

Version G_6.0 2024/01/09

May damage fertility or the unborn child.

• bis(2-(2-methoxyethoxy)ethyl) ether

Carcinogenicity:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

Specific target organ toxicity - single exposure, (STOT-SE):

May cause drowsiness or dizziness.

• γ-butyrolactone

Specific target organ toxicity - repeat exposure, (STOT-RE):

no data available.

Aspiration hazard:

no data available.

12. Ecological information

12.1. Toxicity: No data available.

12.2. Persistence and degradability:

No data available

12.3. Bioaccumulative potential:

No data available

12.4. Mobility in soil:

No data available

12.5. Results of PBT and vPvB assessment:

Has not carried out PBT and vPvB assessment.

12.6. Endocrine disrupting properties:

No data available

12.7. Other adverse effects:

No data available

13. Disposal considerations

13.1. Waste treatment methods

Product: Dispose as hazardous waste. Packaging with product residues must be disposed of

under the same conditions as the product itself.



Version G_6.0

2024/01/09

Recommended waste code: 08 03 12* (waste ink containing dangerous substances)

Uncleaned packaging: 15 01 10* (packaging, the residues of dangerous substances or hazardous waste

contain or are contaminated by dangerous substances or special wastes)

Recommendation: Uncontaminated packaging can be recycled. Non-cleanable packaging must be

disposed of in the same way as the substance.

14. Transport information

14.1 UN Class/UN Number

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.2 UN proper shipping name

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.3 Transport hazard class(es)

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.4 Packing group

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.5 Environmental hazards

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.6. Special precautions for user

ADR/ADG/DOT, IMDG, or IATA: Transport and storage of the product in accordance with general precautions

and instructions mentioned in this SDS.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and IBC code: Not regulated

15. Regulatory information

EU Information: Chemical Safety Assessment according to (EC)1907/2006 This product has not carried out any Chemical Safety Assessment yet.

List of substances subject to SVHC - candidate list

Tetraethylene glycol dimethyl ether (CAS 143-24-8)

International Information:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)



Version G_6.0 2024/01/09

16. Other information

List of relevant H-Statements:

(Reference for Section 3. "Composition/information on ingredients")

- H302: Harmful if swallowed.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H360: May damage fertility or the unborn child.

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and ex erience is ained. Roland DG does not warrant the com-leteness or accuracy of the information contained herein.

Version G_6.0 2024/01/09

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ECO-SOL MAX, ESL3-MG ECO-SOL MAX, ESL3-4MG

1.2. Relevant identified uses of the substance or mixture and uses advised against

Inkjet Printing

1.3. Details of the supplier of the safety data sheet

Manufacturer's name: Roland DG Corporation

Address: 1-1-2 Shinmiyakoda, Hamana-ku, Hamamatsu-shi, Shizuoka-ken, 431-2103

Phone: +81-53-484-1224 FAX: +81-53-484-1226

E-mail:

Revised date: 9-Jan-2024

1.4. Emergency telephone:

2. Hazard identification

2.1. Classification of the substance or mixture

This product is classified as hazardous according to GHS.

Flammable liquids

Acute toxicity (oral)

Skin corrosion/irritation

Category 2

Serious eye damage/eye irritation

Category 1

Reproductive toxicity

Category 1B

2.2. GHS label elements, including precautionary statements

Pictgram(s)



Signal Word: Danger

Hazard Statement:

Combustible liquid.

Version G_6.0 2024/01/09

May be harmful if swallowed.

Causes skin irritation.

Causes serious eye damage.

May damage fertility or the unborn child.

Precautionary statements — **Prevention:**

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements — **Response:**

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Potential Health Effects:

Eyes: Causes severe eye injury which may persist for several days.

Skin: Contact with skin may cause irritation, swelling or redness, allergic sensitization.

Inhalation: Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired

fertility and irritate nose, throat/respiratory system.

Ingestion: May cause injury of mouth, throat, and stomach.

Chronic Health Hazards: Repeated skin contact may cause a persistent irritation or dermatitis.

Carcinogenicity: None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

Others: No information.

3. Composition/information on ingredients

Chemical nature: mixture

Composition	CAS No.	% By Weight	GHS Classification
Colorant	CBI	1-5	Not classified as hazardous
Diethylene glycol diethyl ether	112-36-7	55-65	Skin Irrit. 2: H315
γ-butyrolactone	96-48-0	<20	Acute Tox. 4: H302 Eye Damage 1: H318 STOT Single Exp. 3: H336
bis(2-(2-methoxyethoxy)ethyl) ether	143-24-8	10-20	Repr. 1B: H360
Tetraethylene glycol monobutyl ether	1559-34-8	1-5	Eye Irrit. 2: H319

[†] CBI: Confidential Business Information

[‡] For the full text of the H-Statements mentioned in this Section, see Section 16.

Version G 6.0 2024/01/09

4. First aid measures

4.1. Description of first aid measures

Eyes: In case of contact, immediately flush eyes with plenty of water for several minutes. Hold eyelids open

during flushing. Call a physician.

Skin: In case of contact, immediately flush with plenty of water while removing contaminated clothing and

shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give

oxygen. Call a physician.

If swallowed, DO NOT induce vomiting. Seek immediate medical advice. Ingestion:

4.2. Most important symptoms and effects, both acute and delayed

Eyes: Causes severe eye injury which may persist for several days.

Skin: Contact with skin may cause irritation, swelling or redness, allergic sensitization.

Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired fertility and Inhalation:

irritate nose, throat/respiratory system.

May cause injury of mouth, throat, and stomach. Ingestion:

4.3. Indication of any immediate medical attention and special treatment needed

no information

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Dry chemical, Foam, Carbon dioxide, Dry sand, Loaded stream in spray.

Unsuitable extinguishing media:

Water, High-pressure water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors. Flash Point: > 71deg.C

5.3. Advice for firefighters

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues. Applying direct water may be dangerous because fire may expand to surroundings.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate personal protective equipment.

Version G 6.0 2024/01/09

6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.

6.3. Methods and material for containment and cleaning up

Sweep up material and dispose as waste following local regulations.

6.4. Reference to other sections

Refer to "Section 8 Exposure controls/personal protection" and "Section 13 Disposal consideration" as appropriate.

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Put protection wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with metals, amines, free radical initiators, oxidising agents.

7.3 Specific end use(s): Inkjet Printing

8. Exposure controls/ personal protection

8.1. Control parameters

Occupational Exposure Limits:

Derived No-Effect Level (DNEL)

— Diethylene glycol diethyl ether:

[Long term exposure] 50.05 mg/m³

[Short term exposure] no hazard identified

— γ-butyrolactone:

[Long term exposure] 130 mg/m³

[Short term exposure] 958 mg/m³

8.2. Exposure controls

Appropriate engineering controls

Provide general and/or local exhaust ventilation.

Respiratory protection:

Not requiredwhen sufficient ventilation is provided. In case of inadequate ventilation and exposure limits are exceeded or if irritation or other symptoms are experienced, use a NIOSH/MSHA or European Standard EN149 approved respirator (with activated carbon layer for organic vapour).

Hand protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, use protective gloves. Recommended impervious gloves is EN420/374 approved butyl rubber glove.

Version G_6.0 2024/01/09

Eye protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear EN166 approved safety glasses.

Skin protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear protective clothing.

Hygiene measures:

Wash hands after handling. In case contact with clothing, wash before reuse. Do not eat, drink or smoke in handling or storage area.

Environmental exposure control:

Avoid release to the environment.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Magenta Liquid Odour: slight odor Odour threshold: Not defined pH: Not applicable No data available Melting point/freezing point: Initial boiling point and boiling range: No data available

Flash point: > 71deg.C

Evaporation rate: No data available Flammability (solid, gas) Not applicable Upper/lower flammability or explosive limits: No data available No data available Vapor pressure:

Vapor density: > 1 0.9 - 1.0Relative density: Solubility(ies): soluble

No data available Partition coefficient: n-octanol/water: Auto-ignition temperature: No data available Decomposition temperature: No data available No data available Viscosity: Explosive properties: No data available No data available Oxidizing properties: Volatile organic compounds (VOC) content: 950 grams/L

9.2 Other information

No information.

Version G_6.0 2024/01/09

10. Stability and reactivity

10.1 Reactivity:

No reactivity under normal temperature.

10.2 Chemical stability:

Stable under normal temperature.

10.3 Possibility of hazardous reactions:

Not expected.

10.4 Conditions to avoid:

Elevated temperatures/heat, UV light, when not in use.

10.5 Incompatible materials:

Avoid contact with acids, amines, free radical initiators, oxidizing agents.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity:

γ-butyrolactone

LD50 (oral): 1582mg/kgbw, LD50 (dermal): no data available, LD50 (Inhal.): LC50>5.1mg/L

Serious eye damage/eye irritation:

Causes serious eye damage.

• γ-butyrolactone

Causes serious eye irritation.

• Tetraethylene glycol monobutyl ether

Skin corrosion/irritation:

Causes skin irritation.

• Diethylene glycol diethyl ether

Respiratory or skin sensitisation:

no data available.

Germ cell mutagenicity:

no data available.

Reproductive toxicity:

Version G_6.0 2024/01/09

May damage fertility or the unborn child.

• bis(2-(2-methoxyethoxy)ethyl) ether

Carcinogenicity:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

Specific target organ toxicity - single exposure, (STOT-SE):

May cause drowsiness or dizziness.

• γ-butyrolactone

Specific target organ toxicity - repeat exposure, (STOT-RE):

no data available.

Aspiration hazard:

no data available.

12. Ecological information

12.1. Toxicity: No data available.

12.2. Persistence and degradability:

No data available

12.3. Bioaccumulative potential:

No data available

12.4. Mobility in soil:

No data available

12.5. Results of PBT and vPvB assessment:

Has not carried out PBT and vPvB assessment.

12.6. Endocrine disrupting properties:

No data available

12.7. Other adverse effects:

No data available

13. Disposal considerations

13.1. Waste treatment methods

Product: Dispose as hazardous waste. Packaging with product residues must be disposed of

under the same conditions as the product itself.



Version G_6.0

ECO-SOL MAX, ESL3-MG ECO-SOL MAX, ESL3-4MG

2024/01/09

Recommended waste code: 08 03 12* (waste ink containing dangerous substances)

Uncleaned packaging: 15 01 10* (packaging, the residues of dangerous substances or hazardous waste

contain or are contaminated by dangerous substances or special wastes)

Recommendation: Uncontaminated packaging can be recycled. Non-cleanable packaging must be

disposed of in the same way as the substance.

14. Transport information

14.1 UN Class/UN Number

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.2 UN proper shipping name

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.3 Transport hazard class(es)

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.4 Packing group

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.5 Environmental hazards

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.6. Special precautions for user

ADR/ADG/DOT, IMDG, or IATA: Transport and storage of the product in accordance with general precautions

and instructions mentioned in this SDS.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and IBC code: Not regulated

15. Regulatory information

EU Information: Chemical Safety Assessment according to (EC)1907/2006 This product has not carried out any Chemical Safety Assessment yet.

List of substances subject to SVHC - candidate list

Tetraethylene glycol dimethyl ether (CAS 143-24-8)

International Information:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)



Version G_6.0 2024/01/09

16. Other information

List of relevant H-Statements:

(Reference for Section 3. "Composition/information on ingredients")

- H302: Harmful if swallowed.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H360: May damage fertility or the unborn child.

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and exterior is ained. Roland DG does not warrant the completeness or accuracy of the information contained herein.

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ECO-SOL MAX, ESL3-YE ECO-SOL MAX, ESL3-4YE

Roland

1.2. Relevant identified uses of the substance or mixture and uses advised against

Inkjet Printing

1.3. Details of the supplier of the safety data sheet

Manufacturer's name: Roland DG Corporation

Address: 1-1-2 Shinmiyakoda, Hamana-ku, Hamamatsu-shi, Shizuoka-ken, 431-2103

Phone: +81-53-484-1224 FAX: +81-53-484-1226

E-mail:

Revised date: 9-Jan-2023

1.4. Emergency telephone:

2. Hazard identification

2.1. Classification of the substance or mixture

This product is classified as hazardous according to GHS.

Flammable liquids

Acute toxicity (oral)

Skin corrosion/irritation

Category 2

Serious eye damage/eye irritation

Category 1

Reproductive toxicity

Category 1B

2.2. GHS label elements, including precautionary statements

Pictgram(s)



Signal Word: Danger

Hazard Statement:

Combustible liquid.

Version G_6.0

2024/01/09

May be harmful if swallowed.

Causes skin irritation.

Causes serious eye damage.

May damage fertility or the unborn child.

Precautionary statements — **Prevention:**

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements — **Response:**

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Potential Health Effects:

Eyes: Causes severe eye injury which may persist for several days.

Skin: Contact with skin may cause irritation, swelling or redness, allergic sensitization.

Inhalation: Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired

fertility and irritate nose, throat/respiratory system.

Ingestion: May cause injury of mouth, throat, and stomach.

Chronic Health Hazards: Repeated skin contact may cause a persistent irritation or dermatitis.

Carcinogenicity: This product contains Nickel compounds.IARC evaluated printing ink as a Group 3.(IARC

Group 3: Not classifiable as to carcinogenicity to humans)

Others: No information.

3. Composition/information on ingredients

Chemical nature: mixture

Composition	CAS No.	% By Weight	GHS Classification
Colorant	CBI	1-5	Not classified as hazardous
Diethylene glycol diethyl ether	112-36-7	55-65	Skin Irrit. 2: H315
γ-butyrolactone	96-48-0	<20	Acute Tox. 4: H302 Eye Damage 1: H318 STOT Single Exp. 3: H336
bis(2-(2-methoxyethoxy)ethyl) ether	143-24-8	10-20	Repr. 1B: H360
Tetraethylene glycol monobutyl ether	1559-34-8	1-5	Eye Irrit. 2: H319

[†] CBI: Confidential Business Information

[‡] For the full text of the H-Statements mentioned in this Section, see Section 16.

4. First aid measures

4.1. Description of first aid measures

Eyes: In case of contact, immediately flush eyes with plenty of water for several minutes. Hold eyelids open

during flushing. Call a physician.

Skin: In case of contact, immediately flush with plenty of water while removing contaminated clothing and

shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give

oxygen. Call a physician.

Ingestion: If swallowed, DO NOT induce vomiting. Seek immediate medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Eyes: Causes severe eye injury which may persist for several days.

Skin: Contact with skin may cause irritation, swelling or redness, allergic sensitization.

Inhalation: Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired fertility and

irritate nose, throat/respiratory system.

Ingestion: May cause injury of mouth, throat, and stomach.

4.3. Indication of any immediate medical attention and special treatment needed

no information

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Dry chemical, Foam, Carbon dioxide, Dry sand, Loaded stream in spray.

Unsuitable extinguishing media:

Water, High-pressure water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

Flash Point: > 71deg.C

5.3. Advice for firefighters

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues. Applying direct water may be dangerous because fire may expand to surroundings.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate

Version G 6.0 2024/01/09

personal protective equipment.

6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.

6.3. Methods and material for containment and cleaning up

Sweep up material and dispose as waste following local regulations.

6.4. Reference to other sections

Refer to "Section 8 Exposure controls/ personal protection" and "Section 13 Disposal consideration" as

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Put protection wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with metals, amines, free radical initiators, oxidising agents.

7.3 Specific end use(s): Inkjet Printing

8. Exposure controls/ personal protection

8.1. Control parameters

Occupational Exposure Limits:

Derived No-Effect Level (DNEL)

— Diethylene glycol diethyl ether:

[Long term exposure] 50.05 mg/m³

[Short term exposure] no hazard identified

— γ-butyrolactone:

[Long term exposure] 130 mg/m³

[Short term exposure] 958 mg/m³

8.2. Exposure controls

Appropriate engineering controls

Provide general and/or local exhaust ventilation.

Respiratory protection:

Not required when sufficient ventilation is provided. In case of inadequate ventilation and exposure limits are exceeded or if irritation or other symptoms are experienced, use a NIOSH/MSHA or European Standard EN149 approved respirator (with activated carbon layer for organic vapour).

Hand protection:



Version G_6.0 2024/01/09

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, use protective gloves. Recommended impervious gloves is EN420/374 approved butyl rubber glove.

Eye protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear EN166 approved safety glasses.

Skin protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear protective clothing.

Hygiene measures:

Wash hands after handling. In case contact with clothing, wash before reuse. Do not eat, drink or smoke in handling or storage area.

Environmental exposure control:

Avoid release to the environment.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Yellow Liquid Appearance: Odour: Slightly odour Odour threshold: Not defined Not applicable pH: Melting point/freezing point: No data available Initial boiling point and boiling range: No data available

Flash point: > 71deg.C

Evaporation rate: No data available Not applicable Flammability (solid, gas) Upper/lower flammability or explosive limits: No data available Vapor pressure: No data available

Vapor density: Relative density: 0.9 - 1.0soluble Solubility(ies):

Partition coefficient: n-octanol/water: No data available Auto-ignition temperature: No data available No data available Decomposition temperature: Viscosity: No data available Explosive properties: No data available Oxidizing properties: No data available Volatile organic compounds (VOC) content: 950 grams/L

9.2 Other information

Version G_6.0 2024/01/09

No information.

10. Stability and reactivity

10.1 Reactivity:

No reactivity under normal temperature.

10.2 Chemical stability:

Stable under normal temperature.

10.3 Possibility of hazardous reactions:

Not expected.

10.4 Conditions to avoid:

Elevated temperatures/heat, UV light, when not in use.

10.5 Incompatible materials:

Avoid contact with acids, amines, free radical initiators, oxidizing agents.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity:

 γ -butyrolactone

LD50 (oral): 1582mg/kgbw, LD50 (dermal): no data available, LD50 (Inhal.): LC50>5.1mg/L

Serious eye damage/eye irritation:

Causes serious eye damage.

• γ-butyrolactone

Causes serious eye irritation.

• Tetraethylene glycol monobutyl ether

Skin corrosion/irritation:

Causes skin irritation.

• Diethylene glycol diethyl ether

Respiratory or skin sensitisation:

no data available.

Germ cell mutagenicity:

no data available.

Reproductive toxicity:

May damage fertility or the unborn child.

• bis(2-(2-methoxyethoxy)ethyl) ether

Carcinogenicity:

This product contains Nickel compounds.

IARC evaluated printing ink as a Group 3.

(IARC Group 3: Not classifiable as to carcinogenicity to humans)

Specific target organ toxicity - single exposure, (STOT-SE):

May cause drowsiness or dizziness.

• γ-butyrolactone

Specific target organ toxicity - repeat exposure, (STOT-RE):

no data available.

Aspiration hazard:

no data available.

12. Ecological information

12.1. Toxicity: No data available.

12.2. Persistence and degradability:

No data available

12.3. Bioaccumulative potential:

No data available

12.4. Mobility in soil:

No data available

12.5. Results of PBT and vPvB assessment:

Has not carried out PBT and vPvB assessment.

12.6. Endocrine disrupting properties:

No data available

12.7. Other adverse effects:

No data available

13. Disposal considerations

Version G_6.0

ECO-SOL MAX, ESL3-YE ECO-SOL MAX, ESL3-4YE

2024/01/09

13.1. Waste treatment methods

Product: Dispose as hazardous waste. Packaging with product residues must be disposed of

under the same conditions as the product itself.

Recommended waste code: 08 03 12* (waste ink containing dangerous substances)

Uncleaned packaging: 15 01 10* (packaging, the residues of dangerous substances or hazardous waste

contain or are contaminated by dangerous substances or special wastes)

Recommendation: Uncontaminated packaging can be recycled. Non-cleanable packaging must be

disposed of in the same way as the substance.

14. Transport information

14.1 UN Class/UN Number

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.2 UN proper shipping name

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.3 Transport hazard class(es)

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.4 Packing group

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.5 Environmental hazards

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.6. Special precautions for user

ADR/ADG/DOT, IMDG, or IATA: Transport and storage of the product in accordance with general precautions

and instructions mentioned in this SDS.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and IBC code: Not regulated

15. Regulatory information

EU Information: Chemical Safety Assessment according to (EC)1907/2006

This product has not carried out any Chemical Safety Assessment yet.

List of substances subject to SVHC - candidate list

Tetraethylene glycol dimethyl ether (CAS 143-24-8)

International Information:

This product contains Nickel compounds.

IARC evaluated printing ink as a Group 3.

(IARC Group 3: Not classifiable as to carcinogenicity to humans



Version G_6.0 2024/01/09

16. Other information

List of relevant H-Statements:

(Reference for Section 3. "Composition/information on ingredients")

- H302: Harmful if swallowed.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H360: May damage fertility or the unborn child.

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and experience is gained. Roland DG does not warrant the completeness or accuracy of the information contained herein.

Version G_6.0 2024/01/09

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ECO-SOL MAX, ESL3-BK ECO-SOL MAX, ESL3-4BK

1.2. Relevant identified uses of the substance or mixture and uses advised against

Inkjet Printing

1.3. Details of the supplier of the safety data sheet

Manufacturer's name: Roland DG Corporation

Address: 1-1-2 Shinmiyakoda, Hamana-ku, Hamamatsu-shi, Shizuoka-ken, 431-2103

Phone: +81-53-484-1224 FAX: +81-53-484-1226

E-mail:

Revised date: 9-Jan-2024

1.4. Emergency telephone:

2. Hazard identification

2.1. Classification of the substance or mixture

This product is classified as hazardous according to GHS.

Flammable liquids

Acute toxicity (oral)

Skin corrosion/irritation

Category 2

Serious eye damage/eye irritation

Category 1

Reproductive toxicity

Category 1B

2.2. GHS label elements, including precautionary statements

Pictgram(s)



Signal Word: Danger

Hazard Statement:

Combustible liquid.

Version G 6.0

2024/01/09

May be harmful if swallowed.

Causes skin irritation.

Causes serious eye damage.

May damage fertility or the unborn child.

Precautionary statements — **Prevention:**

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements — Response:

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Potential Health Effects:

Eyes: Causes severe eye injury which may persist for several days.

Skin: Contact with skin may cause irritation, swelling or redness, allergic sensitization.

Inhalation: Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired

fertility and irritate nose, throat/respiratory system.

May cause injury of mouth, throat, and stomach. Ingestion:

Chronic Health Hazards: Repeated skin contact may cause a persistent irritation or dermatitis.

Carcinogenicity: This product contains Carbon black.IARC evaluated printing ink as a Group 3.(IARC

Group 3: Not classifiable as to carcinogenicity to humans)

Others: No information.

3. Composition/information on ingredients

Chemical nature: mixture

Composition	CAS No.	% By Weight	GHS Classification
Carbon Black	1333-86-4	1-5	Not classified as hazardous
Diethylene glycol diethyl ether	112-36-7	55-65	Skin Irrit. 2: H315
γ-butyrolactone	96-48-0	<20	Acute Tox. 4: H302 Eye Damage 1: H318 STOT Single Exp. 3: H336
bis(2-(2-methoxyethoxy)ethyl) ether	143-24-8	10-20	Repr. 1B: H360
Tetraethylene glycol monobutyl ether	1559-34-8	1-5	Eye Irrit. 2: H319

[†] For the full text of the H-Statements mentioned in this Section, see Section 16.

Version G_6.0 2024/01/09

4. First aid measures

4.1. Description of first aid measures

Eyes: In case of contact, immediately flush eyes with plenty of water for several minutes. Hold eyelids open

during flushing. Call a physician.

Skin: In case of contact, immediately flush with plenty of water while removing contaminated clothing and

shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give

oxygen. Call a physician.

Ingestion: If swallowed, DO NOT induce vomiting. Seek immediate medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Eyes: Causes severe eye injury which may persist for several days.

Skin: Contact with skin may cause irritation, swelling or redness, allergic sensitization.

Inhalation: Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired fertility and

irritate nose, throat/respiratory system.

Ingestion: May cause injury of mouth, throat, and stomach.

4.3. Indication of any immediate medical attention and special treatment needed

no information

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Dry chemical, Foam, Carbon dioxide, Dry sand, Loaded stream in spray.

Unsuitable extinguishing media:

Water, High-pressure water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

Flash Point: > 71deg.C

5.3. Advice for firefighters

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues. Applying direct water may be dangerous because fire may expand to surroundings.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate personal protective equipment.

Version G_6.0 2024/01/09

6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.

6.3. Methods and material for containment and cleaning up

Sweep up material and dispose as waste following local regulations.

6.4. Reference to other sections

Refer to "Section 8 Exposure controls/ personal protection" and "Section 13 Disposal consideration" as appropriate.

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Put protection wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with metals, amines, free radical initiators, oxidising agents.

7.3 Specific end use(s): Inkjet Printing

8. Exposure controls/ personal protection

8.1. Control parameters

Occupational Exposure Limits:

Derived No-Effect Level (DNEL)

— Carbon Black:

[Long term exposure] no hazard identified

[Short term exposure] no hazard identified

- Diethylene glycol diethyl ether:

[Long term exposure] 50.05 mg/m³

[Short term exposure] no hazard identified

— γ-butyrolactone:

[Long term exposure] 130 mg/m³

[Short term exposure] 958 mg/m³

8.2. Exposure controls

Appropriate engineering controls

Provide general and/or local exhaust ventilation.

Respiratory protection:

Not requiredwhen sufficient ventilation is provided. In case of inadequate ventilation and exposure limits are exceeded or if irritation or other symptoms are experienced, use a NIOSH/MSHA or European Standard EN149 approved respirator (with activated carbon layer for organic vapour).



Version G 6.0 2024/01/09

Hand protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, use protective gloves. Recommended impervious gloves is EN420/374 approved butyl rubber glove.

Eye protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear EN166 approved safety glasses.

Skin protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear protective clothing.

Hygiene measures:

Wash hands after handling. In case contact with clothing, wash before reuse.Do not eat, drink or smoke in handling or storage area.

Environmental exposure control:

Avoid release to the environment.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Black Liquid Appearance: Odour: Slightly odour Odour threshold: Not defined Not applicable pH: Melting point/freezing point: No data available Initial boiling point and boiling range: No data available

Flash point: > 71deg.C

Evaporation rate: No data available Flammability (solid, gas) Not applicable Upper/lower flammability or explosive limits: No data available Vapor pressure: No data available

> 1 Vapor density: Relative density: 0.9 - 1.0Solubility(ies): soluble

No data available Partition coefficient: n-octanol/water: Auto-ignition temperature: No data available Decomposition temperature: No data available Viscosity: No data available Explosive properties: No data available Oxidizing properties: No data available Volatile organic compounds (VOC) content: 950 gram/L



Version G_6.0 2024/01/09

9.2 Other information

No information.

10. Stability and reactivity

10.1 Reactivity:

No reactivity under normal temperature.

10.2 Chemical stability:

Stable under normal temperature.

10.3 Possibility of hazardous reactions:

Not expected.

10.4 Conditions to avoid:

Elevated temperatures/heat, UV light, when not in use.

10.5 Incompatible materials:

Avoid contact with acids, amines, free radical initiators, oxidizing agents.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity:

γ-butyrolactone

LD50 (oral): 1582mg/kgbw, LD50 (dermal): no data available, LD50 (Inhal.): LC50>5.1mg/L

Serious eye damage/eye irritation:

Causes serious eye damage.

• γ-butyrolactone

Causes serious eye irritation.

• Tetraethylene glycol monobutyl ether

Skin corrosion/irritation:

Causes skin irritation.

• Diethylene glycol diethyl ether

Respiratory or skin sensitisation:

no data available.

Germ cell mutagenicity:

Version G_6.0 2024/01/09

no data available.

Reproductive toxicity:

May damage fertility or the unborn child.

• bis(2-(2-methoxyethoxy)ethyl) ether

Carcinogenicity:

This product contains Carbon black.

IARC evaluated printing ink as a Group 3.

(IARC Group 3: Not classifiable as to carcinogenicity to humans)

Specific target organ toxicity - single exposure, (STOT-SE):

May cause drowsiness or dizziness.

• γ-butyrolactone

Specific target organ toxicity - repeat exposure, (STOT-RE):

no data available.

Aspiration hazard:

no data available.

12. Ecological information

12.1. Toxicity: No data available.

12.2. Persistence and degradability:

No data available

12.3. Bioaccumulative potential:

No data available

12.4. Mobility in soil:

No data available

12.5. Results of PBT and vPvB assessment:

Has not carried out PBT and vPvB assessment.

12.6. Endocrine disrupting properties:

No data available

12.7. Other adverse effects:

No data available

13. Disposal considerations



Version G_6.0

2024/01/09

13.1. Waste treatment methods

Product: Dispose as hazardous waste. Packaging with product residues must be disposed of

under the same conditions as the product itself.

Recommended waste code: 08 03 12* (waste ink containing dangerous substances)

Uncleaned packaging: 15 01 10* (packaging, the residues of dangerous substances or hazardous waste

contain or are contaminated by dangerous substances or special wastes)

Recommendation: Uncontaminated packaging can be recycled. Non-cleanable packaging must be

disposed of in the same way as the substance.

14. Transport information

14.1 UN Class/UN Number

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.2 UN proper shipping name

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.3 Transport hazard class(es)

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.4 Packing group

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.5 Environmental hazards

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.6. Special precautions for user

ADR/ADG/DOT, IMDG, or IATA: Transport and storage of the product in accordance with general precautions

and instructions mentioned in this SDS.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and IBC code: Not regulated

15. Regulatory information

EU Information: Chemical Safety Assessment according to (EC)1907/2006 This product has not carried out any Chemical Safety Assessment yet.

List of substances subject to SVHC - candidate list

Tetraethylene glycol dimethyl ether (CAS 143-24-8)

International Information:

This product contains Carbon black.

IARC evaluated printing ink as a Group 3.

(IARC Group 3: Not classifiable as to carcinogenicity to humans



Version G_6.0 2024/01/09

16. Other information

List of relevant H-Statements:

(Reference for Section 3. "Composition/information on ingredients")

- H302: Harmful if swallowed.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H360: May damage fertility or the unborn child.

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and experience is gained. Roland DG does not warrant the completeness or accuracy of the information contained herein.

Version G_6.0 2024/01/09

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ECO-SOL MAX, ESL3-LC ECO-SOL MAX, ESL3-4LC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Inkjet Printing

1.3. Details of the supplier of the safety data sheet

Manufacturer's name: Roland DG Corporation

Address: 1-1-2 Shinmiyakoda, Hamana-ku, Hamamatsu-shi, Shizuoka-ken, 431-2103

Phone: +81-53-484-1224 FAX: +81-53-484-1226

E-mail:

Revised date: 9-Jan-2024

1.4. Emergency telephone:

2. Hazard identification

2.1. Classification of the substance or mixture

This product is classified as hazardous according to GHS.

Flammable liquids

Acute toxicity (oral)

Skin corrosion/irritation

Category 2

Serious eye damage/eye irritation

Category 1

Reproductive toxicity

Category 1B

2.2. GHS label elements, including precautionary statements

Pictgram(s)



Signal Word: Danger

Hazard Statement:

Combustible liquid.

Version G_6.0

2024/01/09

May be harmful if swallowed.

Causes skin irritation.

Causes serious eye damage.

May damage fertility or the unborn child.

Precautionary statements — **Prevention:**

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements — **Response:**

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Potential Health Effects:

Eyes: Causes severe eye injury which may persist for several days.

Skin: Contact with skin may cause irritation, swelling or redness, allergic sensitization.

Inhalation: Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired

fertility and irritate nose, throat/respiratory system.

Ingestion: May cause injury of mouth, throat, and stomach.

Chronic Health Hazards: Repeated skin contact may cause a persistent irritation or dermatitis.

Carcinogenicity: None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

Others: No information.

3. Composition/information on ingredients

Chemical nature: mixture

Composition	CAS No.	% By Weight	GHS Classification
Colorant	CBI	<1	Not classified as hazardous
Diethylene glycol diethyl ether	112-36-7	55-65	Skin Irrit. 2: H315
γ-butyrolactone	96-48-0	<20	Acute Tox. 4: H302 Eye Damage 1: H318 STOT Single Exp. 3: H336
bis(2-(2-methoxyethoxy)ethyl) ether	143-24-8	10-20	Repr. 1B: H360
Tetraethylene glycol monobutyl ether	1559-34-8	1-5	Eye Irrit. 2: H319

[†] CBI: Confidential Business Information

[‡] For the full text of the H-Statements mentioned in this Section, see Section 16.

Version G_6.0 2024/01/09

4. First aid measures

4.1. Description of first aid measures

Eyes: In case of contact, immediately flush eyes with plenty of water for several minutes. Hold eyelids open

during flushing. Call a physician.

Skin: In case of contact, immediately flush with plenty of water while removing contaminated clothing and

shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give

oxygen. Call a physician.

Ingestion: If swallowed, DO NOT induce vomiting. Seek immediate medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Eyes: Causes severe eye injury which may persist for several days.

Skin: Contact with skin may cause irritation, swelling or redness, allergic sensitization.

Inhalation: Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired fertility and

irritate nose, throat/respiratory system.

Ingestion: May cause injury of mouth, throat, and stomach.

4.3. Indication of any immediate medical attention and special treatment needed

no information

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Dry chemical, Foam, Carbon dioxide, Dry sand, Loaded stream in spray.

Unsuitable extinguishing media:

Water, High-pressure water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors. Flash Point: > 71deg.C

5.3. Advice for firefighters

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues. Applying direct water may be dangerous because fire may expand to surroundings.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate personal protective equipment.

ECO-SOL MAX, ESL3-LC ECO-SOL MAX, ESL3-4LC

Version G_6.0 2024/01/09

6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.

6.3. Methods and material for containment and cleaning up

Sweep up material and dispose as waste following local regulations.

6.4. Reference to other sections

Refer to "Section 8 Exposure controls/ personal protection" and "Section 13 Disposal consideration" as appropriate.

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Put protection wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with metals, amines, free radical initiators, oxidising agents.

7.3 Specific end use(s): Inkjet Printing

8. Exposure controls/ personal protection

8.1. Control parameters

Occupational Exposure Limits:

Derived No-Effect Level (DNEL)

— Diethylene glycol diethyl ether:

[Long term exposure] 50.05 mg/m³

[Short term exposure] no hazard identified

— γ-butyrolactone:

[Long term exposure] 130 mg/m³

[Short term exposure] 958 mg/m³

8.2. Exposure controls

Appropriate engineering controls

Provide general and/or local exhaust ventilation.

Respiratory protection:

Not requiredwhen sufficient ventilation is provided. In case of inadequate ventilation and exposure limits are exceeded or if irritation or other symptoms are experienced, use a NIOSH/MSHA or European Standard EN149 approved respirator (with activated carbon layer for organic vapour).

Hand protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, use protective gloves. Recommended impervious gloves is EN420/374 approved butyl rubber glove.

ECO-SOL MAX, ESL3-LC ECO-SOL MAX, ESL3-4LC

Version G_6.0 2024/01/09

Eye protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear EN166 approved safety glasses.

Skin protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear protective clothing.

Hygiene measures:

Wash hands after handling. In case contact with clothing, wash before reuse. Do not eat, drink or smoke in handling or storage area.

Environmental exposure control:

Avoid release to the environment.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Cyan Liquid
Odour: Slightly odour
Odour threshold: Not defined
pH: Not applicable
Melting point/freezing point: No data available
Initial boiling point and boiling range: No data available

Flash point: > 71deg.C

Evaporation rate: No data available Flammability (solid, gas) Not applicable Upper/lower flammability or explosive limits: No data available Vapor pressure: No data available

Vapor density: > 1
Relative density: 0.9-1.0
Solubility(ies): soluble

Partition coefficient: n-octanol/water:

Auto-ignition temperature:

Decomposition temperature:

Viscosity:

Explosive properties:

Oxidizing properties:

Volatile organic compounds (VOC) content:

No data available
No data available
No data available

9.2 Other information

No information.

ECO-SOL MAX, ESL3-LC ECO-SOL MAX, ESL3-4LC Version G_6.0 2024/01/09

10. Stability and reactivity

10.1 Reactivity:

No reactivity under normal temperature.

10.2 Chemical stability:

Stable under normal temperature.

10.3 Possibility of hazardous reactions:

Not expected.

10.4 Conditions to avoid:

Elevated temperatures/heat, UV light, when not in use.

10.5 Incompatible materials:

Avoid contact with acids, amines, free radical initiators, oxidizing agents.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity:

γ-butyrolactone

LD50 (oral): 1582mg/kgbw, LD50 (dermal): no data available, LD50 (Inhal.): LC50>5.1mg/L

Serious eye damage/eye irritation:

Causes serious eye damage.

• γ-butyrolactone

Causes serious eye irritation.

• Tetraethylene glycol monobutyl ether

Skin corrosion/irritation:

Causes skin irritation.

• Diethylene glycol diethyl ether

Respiratory or skin sensitisation:

no data available.

Germ cell mutagenicity:

no data available.

Reproductive toxicity:

ECO-SOL MAX, ESL3-LC ECO-SOL MAX, ESL3-4LC

Version G_6.0 2024/01/09

May damage fertility or the unborn child.

• bis(2-(2-methoxyethoxy)ethyl) ether

Carcinogenicity:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

Specific target organ toxicity - single exposure, (STOT-SE):

May cause drowsiness or dizziness.

• γ-butyrolactone

Specific target organ toxicity - repeat exposure, (STOT-RE):

no data available.

Aspiration hazard:

no data available.

12. Ecological information

12.1. Toxicity: No data available.

12.2. Persistence and degradability:

No data available

12.3. Bioaccumulative potential:

No data available

12.4. Mobility in soil:

No data available

12.5. Results of PBT and vPvB assessment:

Has not carried out PBT and vPvB assessment.

12.6. Endocrine disrupting properties:

No data available

12.7. Other adverse effects:

No data available

13. Disposal considerations

13.1. Waste treatment methods

Product: Dispose as hazardous waste. Packaging with product residues must be disposed of

under the same conditions as the product itself.



Version G_6.0

ECO-SOL MAX, ESL3-LC ECO-SOL MAX, ESL3-4LC

2024/01/09

Recommended waste code: 08 03 12* (waste ink containing dangerous substances)

Uncleaned packaging: 15 01 10* (packaging, the residues of dangerous substances or hazardous waste

contain or are contaminated by dangerous substances or special wastes)

Recommendation: Uncontaminated packaging can be recycled. Non-cleanable packaging must be

disposed of in the same way as the substance.

14. Transport information

14.1 UN Class/UN Number

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.2 UN proper shipping name

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.3 Transport hazard class(es)

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.4 Packing group

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.5 Environmental hazards

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.6. Special precautions for user

ADR/ADG/DOT, IMDG, or IATA: Transport and storage of the product in accordance with general precautions

and instructions mentioned in this SDS.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and IBC code: Not regulated

15. Regulatory information

EU Information: Chemical Safety Assessment according to (EC)1907/2006 This product has not carried out any Chemical Safety Assessment yet.

List of substances subject to SVHC - candidate list

Tetraethylene glycol dimethyl ether (CAS 143-24-8)

International Information:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)



ECO-SOL MAX, ESL3-LC ECO-SOL MAX, ESL3-4LC

Version G_6.0 2024/01/09

16. Other information

List of relevant H-Statements:

(Reference for Section 3. "Composition/information on ingredients")

- H302: Harmful if swallowed.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H360: May damage fertility or the unborn child.

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and ex erience is ained. Roland DG does not warrant the com-leteness or accuracy of the information contained herein.

Version G_6.0 2024/01/09

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ECO-SOL MAX, ESL3-LM ECO-SOL MAX, ESL3-4LM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Inkjet Printing

1.3. Details of the supplier of the safety data sheet

Manufacturer's name: Roland DG Corporation

Address: 1-1-2 Shinmiyakoda, Hamana-ku, Hamamatsu-shi, Shizuoka-ken, 431-2103

Phone: +81-53-484-1224 FAX: +81-53-484-1226

E-mail:

Revised date: 9-Jan-2024

1.4. Emergency telephone:

2. Hazard identification

2.1. Classification of the substance or mixture

This product is classified as hazardous according to GHS.

Flammable liquids

Acute toxicity (oral)

Skin corrosion/irritation

Category 2

Serious eye damage/eye irritation

Category 1

Reproductive toxicity

Category 1B

2.2. GHS label elements, including precautionary statements

Pictgram(s)



Signal Word: Danger

Hazard Statement:

Combustible liquid.

ECO-SOL MAX, ESL3-LM ECO-SOL MAX, ESL3-4LM Version G_6.0 2024/01/09

May be harmful if swallowed.

Causes skin irritation.

Causes serious eye damage.

May damage fertility or the unborn child.

Precautionary statements — **Prevention:**

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements — Response:

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Potential Health Effects:

Eyes: Causes severe eye injury which may persist for several days.

Skin: Contact with skin may cause irritation, swelling or redness, allergic sensitization.

Inhalation: Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired

fertility and irritate nose, throat/respiratory system.

Ingestion: May cause injury of mouth, throat, and stomach.

Chronic Health Hazards: Repeated skin contact may cause a persistent irritation or dermatitis.

Carcinogenicity: None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

Others: No information.

3. Composition/information on ingredients

Chemical nature: mixture

Composition	CAS No.	% By Weight	GHS Classification
Colorant	CBI	1-5	Not classified as hazardous
Diethylene glycol diethyl ether	112-36-7	55-65	Skin Irrit. 2: H315
γ-butyrolactone	96-48-0	<20	Acute Tox. 4: H302 Eye Damage 1: H318 STOT Single Exp. 3: H336
bis(2-(2-methoxyethoxy)ethyl) ether	143-24-8	10-20	Repr. 1B: H360
Tetraethylene glycol monobutyl ether	1559-34-8	1-5	Eye Irrit. 2: H319

[†] CBI: Confidential Business Information

[‡] For the full text of the H-Statements mentioned in this Section, see Section 16.

ECO-SOL MAX, ESL3-LM ECO-SOL MAX, ESL3-4LM

Version G_6.0 2024/01/09

4. First aid measures

4.1. Description of first aid measures

Eyes: In case of contact, immediately flush eyes with plenty of water for several minutes. Hold eyelids open

during flushing. Call a physician.

Skin: In case of contact, immediately flush with plenty of water while removing contaminated clothing and

shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give

oxygen. Call a physician.

Ingestion: If swallowed, DO NOT induce vomiting. Seek immediate medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Eyes: Causes severe eye injury which may persist for several days.

Skin: Contact with skin may cause irritation, swelling or redness, allergic sensitization.

Inhalation: Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired fertility and

irritate nose, throat/respiratory system.

Ingestion: May cause injury of mouth, throat, and stomach.

4.3. Indication of any immediate medical attention and special treatment needed

no information

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Dry chemical, Foam, Carbon dioxide, Dry sand, Loaded stream in spray.

Unsuitable extinguishing media:

Water, High-pressure water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors. Flash Point: > 71deg.C

5.3. Advice for firefighters

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues. Applying direct water may be dangerous because fire may expand to surroundings.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate personal protective equipment.

ECO-SOL MAX, ESL3-LM ECO-SOL MAX, ESL3-4LM

Version G 6.0 2024/01/09

6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.

6.3. Methods and material for containment and cleaning up

Sweep up material and dispose as waste following local regulations.

6.4. Reference to other sections

Refer to "Section 8 Exposure controls/personal protection" and "Section 13 Disposal consideration" as appropriate.

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Put protection wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with metals, amines, free radical initiators, oxidising agents.

7.3 Specific end use(s): Inkjet Printing

8. Exposure controls/ personal protection

8.1. Control parameters

Occupational Exposure Limits:

Derived No-Effect Level (DNEL)

— Diethylene glycol diethyl ether:

[Long term exposure] 50.05 mg/m³

[Short term exposure] no hazard identified

— γ-butyrolactone:

[Long term exposure] 130 mg/m³

[Short term exposure] 958 mg/m³

8.2. Exposure controls

Appropriate engineering controls

Provide general and/or local exhaust ventilation.

Respiratory protection:

Not requiredwhen sufficient ventilation is provided. In case of inadequate ventilation and exposure limits are exceeded or if irritation or other symptoms are experienced, use a NIOSH/MSHA or European Standard EN149 approved respirator (with activated carbon layer for organic vapour).

Hand protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, use protective gloves. Recommended impervious gloves is EN420/374 approved butyl rubber glove.

Version G_6.0 2024/01/09

Eye protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear EN166 approved safety glasses.

Skin protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear protective clothing.

Hygiene measures:

Wash hands after handling. In case contact with clothing, wash before reuse. Do not eat, drink or smoke in handling or storage area.

Environmental exposure control:

Avoid release to the environment.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance: Magenta Liquid
Odour: Slightly odour
Odour threshold: Not defined
pH: Not applicable
Melting point/freezing point: No data available
Initial boiling point and boiling range: No data available

Flash point: >71deg.C

Evaporation rate: No data available Flammability (solid, gas) Not applicable Upper/lower flammability or explosive limits: No data available Vapor pressure: No data available

Vapor density: > 1
Relative density: 0.9-1.0
Solubility(ies): soluble

Partition coefficient: n-octanol/water:

Auto-ignition temperature:

No data available

Decomposition temperature:

No data available

Viscosity:

No data available

Explosive properties:

No data available

No data available

No data available

Volatile organic compounds (VOC) content: 950 g/L

9.2 Other information

No information.



ECO-SOL MAX, ESL3-LM ECO-SOL MAX, ESL3-4LM

Version G_6.0 2024/01/09

10. Stability and reactivity

10.1 Reactivity:

No reactivity under normal temperature.

10.2 Chemical stability:

Stable under normal temperature.

10.3 Possibility of hazardous reactions:

Not expected.

10.4 Conditions to avoid:

Elevated temperatures/heat, UV light, when not in use.

10.5 Incompatible materials:

Avoid contact with acids, amines, free radical initiators, oxidizing agents.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity:

γ-butyrolactone

LD50 (oral): 1582mg/kgbw, LD50 (dermal): no data available, LD50 (Inhal.): LC50>5.1mg/L

Serious eye damage/eye irritation:

Causes serious eye damage.

• γ-butyrolactone

Causes serious eye irritation.

• Tetraethylene glycol monobutyl ether

Skin corrosion/irritation:

Causes skin irritation.

• Diethylene glycol diethyl ether

Respiratory or skin sensitisation:

no data available.

Germ cell mutagenicity:

no data available.

Reproductive toxicity:

ECO-SOL MAX, ESL3-LM ECO-SOL MAX, ESL3-4LM

Version G_6.0 2024/01/09

May damage fertility or the unborn child.

• bis(2-(2-methoxyethoxy)ethyl) ether

Carcinogenicity:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

Specific target organ toxicity - single exposure, (STOT-SE):

May cause drowsiness or dizziness.

• γ-butyrolactone

Specific target organ toxicity - repeat exposure, (STOT-RE):

no data available.

Aspiration hazard:

no data available.

12. Ecological information

12.1. Toxicity: No data available.

12.2. Persistence and degradability:

No data available

12.3. Bioaccumulative potential:

No data available

12.4. Mobility in soil:

No data available

12.5. Results of PBT and vPvB assessment:

Has not carried out PBT and vPvB assessment.

12.6. Endocrine disrupting properties:

No data available

12.7. Other adverse effects:

No data available

13. Disposal considerations

13.1. Waste treatment methods

Product: Dispose as hazardous waste. Packaging with product residues must be disposed of

under the same conditions as the product itself.



ECO-SOL MAX, ESL3-LM ECO-SOL MAX, ESL3-4LM Version G_6.0

2024/01/09

Recommended waste code: 08 03 12* (waste ink containing dangerous substances)

Uncleaned packaging: 15 01 10* (packaging, the residues of dangerous substances or hazardous waste

contain or are contaminated by dangerous substances or special wastes)

Recommendation: Uncontaminated packaging can be recycled. Non-cleanable packaging must be

disposed of in the same way as the substance.

14. Transport information

14.1 UN Class/UN Number

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.2 UN proper shipping name

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.3 Transport hazard class(es)

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.4 Packing group

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.5 Environmental hazards

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.6. Special precautions for user

ADR/ADG/DOT, IMDG, or IATA: Transport and storage of the product in accordance with general precautions

and instructions mentioned in this SDS.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and IBC code: Not regulated

15. Regulatory information

EU Information: Chemical Safety Assessment according to (EC)1907/2006 This product has not carried out any Chemical Safety Assessment yet.

List of substances subject to SVHC - candidate list

Tetraethylene glycol dimethyl ether (CAS 143-24-8)

International Information:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B



ECO-SOL MAX, ESL3-LM ECO-SOL MAX, ESL3-4LM

Version G_6.0 2024/01/09

16. Other informat

List of relevant H-Statements:

(Reference for Section 3. "Composition/information on ingredients")

- H302: Harmful if swallowed.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H360: May damage fertility or the unborn child.

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and ex erience is ained. Roland DG does not warrant the com-leteness or accuracy of the information contained herein.



Version G_6.0

Safety Data Sheet

1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

ECO-SOL MAX, ESL3-MT

Roland

1.2. Relevant identified uses of the substance or mixture and uses advised against

Inkjet Printing

1.3. Details of the supplier of the safety data sheet

Manufacturer's name: Roland DG Corporation

1-1-2 Shinmiyakoda, Hamana-ku, Hamamatsu-shi, Shizuoka-ken, 431-2103

Phone: +81-53-484-1224 FAX: +81-53-484-1226

E-mail:

Revised date: 9-Jan-2024

1.4. Emergency telephone:

2. Hazard identification

2.1. Classification of the substance or mixture

This product is classified as hazardous according to GHS.

Flammable liquids Category 4 Acute toxicity (oral) Category 5 Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 1 Reproductive toxicity Category 1B

2.2. GHS label elements, including precautionary statements

Pictgram(s)



Signal Word: Danger

Hazard Statement:

Combustible liquid.

May be harmful if swallowed.

Causes skin irritation.

Causes serious eye damage.

May damage fertility or the unborn child.

Precautionary statements — **Prevention:**

Do not handle until all safety precautions have been read and understood.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements — Response:

IF ON SKIN: Wash with plenty of soap and water.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

2.3. Other hazards

Potential Health Effects:

Causes severe eye injury which may persist for several days. Eyes:

Skin: Contact with skin may cause irritation, swelling or redness, allergic sensitization.

Inhalation: Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired

fertility and irritate nose, throat/respiratory system.

Ingestion: May cause injury of mouth, throat, and stomach.

Chronic Health Hazards: Repeated skin contact may cause a persistent irritation or dermatitis.

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B) Carcinogenicity:

Others: No information.

3. Composition/information on ingredients

Chemical nature: mixture

Composition	CAS No.	% By Weight	GHS Classification
Diethylene glycol diethyl ether	112-36-7	65-75	Skin Irrit. 2: H315
γ-butyrolactone	96-48-0	5-15	Acute Tox. 4: H302 Eye Damage 1: H318 STOT Single Exp. 3: H336
bis(2-(2-methoxyethoxy)ethyl) ether	143-24-8	10-20	Repr. 1B: H360
Tetraethylene glycol monobutyl ether	1559-34-8	1-5	Eye Irrit. 2: H319

[†] For the full text of the H-Statements mentioned in this Section, see Section 16.

4. First aid measures

4.1. Description of first aid measures

Eyes: In case of contact, immediately flush eyes with plenty of water for several minutes. Hold eyelids open

Version G 6.0

2024/01/09

ECO-SOL MAX, ESL3-MT

during flushing. Call a physician.

Skin: In case of contact, immediately flush with plenty of water while removing contaminated clothing and

shoes. Wash contaminated clothing before reuse. If swelling or redness occurs, call a physician.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give

oxygen. Call a physician.

Ingestion: If swallowed, DO NOT induce vomiting. Seek immediate medical advice.

4.2. Most important symptoms and effects, both acute and delayed

Eyes: Causes severe eye injury which may persist for several days.

Skin: Contact with skin may cause irritation, swelling or redness, allergic sensitization.

Inhalation: Exposure to vapors (mist) may be harmful to the unborn child and at the risk of impaired fertility and

irritate nose, throat/respiratory system.

May cause injury of mouth, throat, and stomach. Ingestion:

4.3. Indication of any immediate medical attention and special treatment needed

no information

5. Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Dry chemical, Foam, Carbon dioxide, Dry sand, Loaded stream in spray.

Unsuitable extinguishing media:

Water, High-pressure water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

Flash Point: > 71deg.C

5.3. Advice for firefighters

Wear special chemical protective clothing and positive pressure self-contained breathing apparatus (SCBA). Approach fire from upwind to avoid hazardous vapors and toxic decomposition products. Decontaminate or discard any clothing that may contain chemical residues. Applying direct water may be dangerous because fire may expand to surroundings.

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate personnel, thoroughly ventilate area, use self-contained breathing apparatus and wear appropriate personal protective equipment.

6.2. Environmental precautions

Wipe off spillage. Prevent liquid from entering sewers, waterways or low areas.

6.3. Methods and material for containment and cleaning up

Sweep up material and dispose as waste following local regulations.

6.4. Reference to other sections

Refer to "Section 8 Exposure controls/ personal protection" and "Section 13 Disposal consideration" as appropriate.

7. Handling and storage

7.1 Precautions for safe handling

Avoid contact with eyes, skin and clothing. Use proper ventilation and no fire in work place. Put protection wear that has electrical conductivity in case of work. Keep out of reach of children and do not drink.

7.2 Conditions for safe storage, including any incompatibilities

Keep containers tightly closed. Do not store the product in high or freezing temperatures. Keep the product out of direct sunlight. Do not store the product with metals, amines, free radical initiators, oxidising agents.

7.3 Specific end use(s): Inkjet Printing

8. Exposure controls/ personal protection

8.1. Control parameters

Occupational Exposure Limits:

Derived No-Effect Level (DNEL)

— Diethylene glycol diethyl ether:

[Long term exposure] 50.05 mg/m³

[Short term exposure] no hazard identified

— γ-butyrolactone:

[Long term exposure] 130 mg/m³

[Short term exposure] 958 mg/m³

8.2. Exposure controls

Appropriate engineering controls

Provide general and/or local exhaust ventilation.

Respiratory protection:

Not requiredwhen sufficient ventilation is provided. In case of inadequate ventilation and exposure limits are exceeded or if irritation or other symptoms are experienced, use a NIOSH/MSHA or European Standard EN149 approved respirator (with activated carbon layer for organic vapour).

Hand protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, use protective gloves. Recommended impervious gloves is EN420/374 approved butyl rubber glove.

Eye protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the

ECO-SOL MAX, ESL3-MT

ink, wear EN166 approved safety glasses.

Skin protection:

Not required under suitable use as setting the ink on the printer. However, in case of direct contact to the ink, wear protective clothing.

Hygiene measures:

Wash hands after handling. In case contact with clothing, wash before reuse. Do not eat, drink or smoke in handling or storage area.

Environmental exposure control:

Avoid release to the environment.

9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Silver Liquid Appearance: Odour: Slightly odour Odour threshold: Not defined рН: Not applicable Melting point/freezing point: No data available Initial boiling point and boiling range: No data available

Flash point: > 71deg.C

Evaporation rate: No data available Flammability (solid, gas) Not applicable Upper/lower flammability or explosive limits: No data available No data available Vapor pressure:

> 1 Vapor density: 0.9 - 1.0Relative density: Solubility(ies): soluble

Partition coefficient: n-octanol/water: No data available Auto-ignition temperature: No data available Decomposition temperature: No data available Viscosity: No data available Explosive properties: No data available Oxidizing properties: No data available

Volatile organic compounds (VOC) content: 950 g/L

9.2 Other information

No information.

10. Stability and reactivity

10.1 Reactivity:

ECO-SOL MAX, ESL3-MT

No reactivity under normal temperature.

10.2 Chemical stability:

Stable under normal temperature.

10.3 Possibility of hazardous reactions:

Not expected.

10.4 Conditions to avoid:

Elevated temperatures/heat, UV light, when not in use.

10.5 Incompatible materials:

Avoid contact with acids, amines, free radical initiators, oxidizing agents.

10.6 Hazardous decomposition products:

Carbon monoxide, carbon dioxide, oxides of nitrogen, toxic gases/vapors.

11. Toxicological information

11.1. Information on toxicological effects

Acute toxicity:

γ-butyrolactone

LD50 (oral): 1582mg/kgbw, LD50 (dermal): no data available, LD50 (Inhal.): LC50>5.1mg/L

Serious eye damage/eye irritation:

Causes serious eye damage.

• γ-butyrolactone

Causes serious eye irritation.

• Tetraethylene glycol monobutyl ether

Skin corrosion/irritation:

Causes skin irritation.

• Diethylene glycol diethyl ether

Respiratory or skin sensitisation:

no data available.

Germ cell mutagenicity:

no data available.

Reproductive toxicity:

May damage fertility or the unborn child.

• bis(2-(2-methoxyethoxy)ethyl) ether



Carcinogenicity:

Roland

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B)

Specific target organ toxicity - single exposure, (STOT-SE):

May cause drowsiness or dizziness.

• γ-butyrolactone

Specific target organ toxicity - repeat exposure, (STOT-RE):

no data available.

Aspiration hazard:

no data available.

12. Ecological information

12.1. Toxicity: No data available.

12.2. Persistence and degradability:

No data available

12.3. Bioaccumulative potential:

No data available

12.4. Mobility in soil:

No data available

12.5. Results of PBT and vPvB assessment:

Has not carried out PBT and vPvB assessment.

12.6. Endocrine disrupting properties:

No data available

12.7. Other adverse effects:

No data available

13. Disposal considerations

13.1. Waste treatment methods

Product: Dispose as hazardous waste. Packaging with product residues must be disposed of

under the same conditions as the product itself.

Recommended waste code: 08 03 12* (waste ink containing dangerous substances)

15 01 10* (packaging, the residues of dangerous substances or hazardous waste Uncleaned packaging:

Version G_6.0

2024/01/09

ECO-SOL MAX, ESL3-MT

contain or are contaminated by dangerous substances or special wastes)

Recommendation: Uncontaminated packaging can be recycled. Non-cleanable packaging must be

disposed of in the same way as the substance.

14. Transport information

14.1 UN Class/UN Number

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.2 UN proper shipping name

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.3 Transport hazard class(es)

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.4 Packing group

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.5 Environmental hazards

ADR/ADG/DOT, IMDG, or IATA: Not regulated

14.6. Special precautions for user

ADR/ADG/DOT, IMDG, or IATA: Transport and storage of the product in accordance with general precautions

and instructions mentioned in this SDS.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and IBC code: Not regulated

15. Regulatory information

EU Information: Chemical Safety Assessment according to (EC)1907/2006

This product has not carried out any Chemical Safety Assessment yet.

List of substances subject to SVHC - candidate list

Tetraethylene glycol dimethyl ether (CAS 143-24-8)

International Information:

None of the ingredients in this ink is listed by IARC as a carcinogen. (1, 2A and 2B



Version G_6.0

2024/01/09

ECO-SOL MAX, ESL3-MT

16. Other information

List of relevant H-Statements:

(Reference for Section 3. "Composition/information on ingredients")

- H302: Harmful if swallowed.
- H315: Causes skin irritation.
- H318: Causes serious eye damage.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H360: May damage fertility or the unborn child.

The information in this Safety Data Sheet (SDS) is believed to be correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. It is subject to revision as additional knowledge and experience is gained. Roland DG does not warrant the completeness or accuracy of the information contained herein.